



# PETROLEUM EQUIPMENT SERVICES LTD

SUPPLIERS TO THE PETROLEUM & CHEMICAL INDUSTRIES

Phone: 64 (09) 414 1119 Fax: 64 (09) 414 1120 www.pes.co.nz



**JL9811**

## Mini-Grease Pump

### No. JL9811

- A highly portable manual greasing pump
- Fit a standard 7 lb. pail
- Dust cover: ID 173mm; follower plate: OD 162mm
- Spring foot load plunger for priming the grease control valve
- By a switch for the high volume and the high pressure deliveries
- One hand grease control valve with rigid tube and 3 jaws coupler
- With 6.5ft hose

### No. JL9811-1

- With 1gal. Pail



**JL9811-1**

**JL9812**

## T-Handle Grease Pump

### No. JL9812

- Fit all 35 lb. pails
- Dust cover: ID 311mm; follower plate: OD 292mm
- More economical than air operated pumps
- With 10ft hose

## Lever Active Grease Pump

### No. JL9812-1



**JL9812-1**

**JL9813**

## Mini-Grease Pump with adjustable length

### No. JL9813

- An improved version of mini-grease pumps of No. JL9811
- With an adjustable plunger tube from 210mm to 270mm
- Dust cover: ID 230mm
- Two optional follower plates: OD 190mm or OD 210mm




**JL9341**

### Grease Pump

**No. JL9341**

- For 20/25kg pails
- 140cm flexible hose, rigid tube
- Cover diameter: 315mm
- Follower diameter: 273mm



**JL9341-1**

**No. JL9341-1**

- For bulk filling of grease guns
- Pump fits 25-50lb. pails
- Including metal dust cover, follower plate & filler nipple



**JL9342**

### Lever Action Oil Dispenser

**No. JL9342**

- Dispenses 2oz. of fluid per stroke
- 48" PVC hose pipe with nozzle
- Cover diameter: 315mm
- Designed for use with 25 to 50 lb. /5 gal. containers



**JL5316**

### Screw Cap with Tap

**No. JL5316**

- Screw cap with DIN51(53mm) tap used for plastic jerrican



**JL5381-JL5386**

### Ball Valves, brass

**No. JL5381**

- 1/4" inlet / outlet

**No. JL5381A**

- 3/8" inlet / outlet

**No. JL5382**

- 1/2" inlet / outlet

**No. JL5383**

- 3/4" inlet / outlet

**No. JL5384**

- 1" inlet / outlet

**No. JL5385**

- 1-1/2" inlet / outlet

**No. JL5386**

- 2" inlet / outlet



**JL5221**



**JL5220**

### Grease Control Valve

**No. JL5221**

- With rigid tube and 3 jaw super grip hydraulic coupler

- Boost greasing pressure to over 6500 PSI

- Provides a functional advantage in tough greasing situations

**No. JL5222**

- Same as JL5221 but with flexible hose and jaws hydraulic coupler



**JL5222**

### Z-Swivel for grease control valve

**No. JL5220 for JL5221 and JL5222**

- Z-swivel (M)X(M) 1/4" or (M)X(F) 1/4"

- Allows the rotation of the control valve in different planes even when all the system is under pressure



## Air Grease Gun



**JL LB-4500**

### Single Shot Air Grease Gun

- 40:1 ratio air motor
- Heavy duty cast aluminium body, for maximum durability & longer service life
- 3-way loading-bulk, filler pump or 16oz. cartridge
- Bleeder valve for purging unwanted air
- Durable follower rod & spring for consistent priming
- Positive grip follower handle
- 4-Jaw super grip coupler for better grip and longer service life
- Nonslip knurled for better grip



**JL LB-4501**

### Continuous Air Grease Gun

- Heavy duty cast aluminum body for maximum durability & longer service life.
- 3-way loading-bulk, filler pump or 16oz grease cartridge.
- Bleeder valve for purging unwanted air.
- Input working pressure: 40 - 100 psi
- Output working pressure: 3800 psi
- Air Inlet: 1/4"
- Weight: 1.6 kgs



**JL LB-500FC**

### Fiber Composite Air Grease Gun

- 40:1 ratio air motor
- Heavy duty fiber composite body for durability and long life
- 3-way loading-bulk, filler pump or 16oz. cartridge
- Bleeder valve for purging unwanted air
- 4Jaw super grip coupler for better grip and longer service life
- Non-slip knurled for better grip
- Weight: only 1.2kg



## Hand-operated Grease Gun



**JL LB-3500**

### Lever Type Grease Gun

- Capacity: 500 cc (Bulk)
- 16 oz (Cartridge)
- Working Pressure: 4500 P.S.I.



**JL LB-3481LN**

### Variable Stroke Pistol Grip Grease Gun

- Heavy duty cast aluminum pump head for maximum durability & longer service life.
- Ergonomic handle design.
- Bleeder valve for purging unwanted air
- Use standard 16oz grease cartridge.
- 4-Jaw super grip coupler for better grip & extended service life, coupler Includes ball check.
- Non-Slip finish for better grip.
- Max pressure: 8000 P.S.I.



**JL LB-3491H**

### 2 Way Adjustment Lever Grease Gun

- Heavy duty cast iron head construction for maximum durability and longer service life. (FCD 25)
- 3-way loading-bulk, filler nipple or 16oz standard grease cartridge.
- Durable follower rod & spring for consistent priming.
- 4-Jaw super grip coupler for better grip and longer service life coupler. Includes ball check.
- Bleeder valve for purging unwanted air.
- Non-Slip finish for better grip.
- Adjustment for high-pressure or high-volume operation.
- Pressure capabilities:
  - 7000 P.S.I. (Volume adjustment)
  - 12000 P.S.I. (Pressure adjustment)