

SPRING DRIVEN HOSE REEL - 2950 SERIES

- ♣ Designed to transfer air, water, oil and grease
- ♣ Perfect for application in industries, vehicle repair & maintenance workshops
- ♣ Compact size and easy installation
- ♣ Spring tension easily adjustable from the outside
- ♣ Fast & easy to service
- ♣ Simple hose replacement without dismantling the reel



Item No.	Application	Inlet/Outlet (Fitting)	Max. Pressure (bar/psi)	Hose Capacity		Packing Dimensions(cm)	NW/GW (kgs)
				I.D.(inch)	Length(ft/m)		
29507154-PU	Air reel	1/2"	12 bar / 180 psi	1/2"	50'/15	54x53x19	24/26
29507154-PVC	Air reel	1/2"	20 bar / 300 psi	1/2"	50'/15	54x53x19	24/26
29507154-R	Air reel	1/2"	20 bar / 300 psi	1/2"	50'/15	54x53x19	24/26
29507153-PVC	Air reel	3/8"	20 bar / 300 psi	3/8"	50'/15	54x53x19	24/26
29507153-R	Air reel	3/8"	20 bar / 300 psi	3/8"	50'/15	54x53x19	24/26
29508154-R1	Oil reel	1/2"	138 bar / 2000 psi	1/2"	50'/15	54x53x19	24/26
29508153-R1	Oil reel	3/8"	155 bar / 2250 psi	3/8"	50'/15	54x53x19	24/26
29509152-R2	Grease reel	1/4"	345 bar / 5000 psi	1/4"	50'/15	54x53x19	24/26

29508153
29508154
29509152

SPRING DRIVEN HOSE REEL - 850 SERIES

- ♣ Heavy ribbed steel plate to ensure strong support
- ♣ Spring located in the middle to ensure stability of the reel
- ♣ Four-direction non-slag hose rollers reduce hose wear
- ♣ Adjustable arm guide (wall, floor, ceiling and pit)
- ♣ Spring fully enclosed and lubricated

Item No.	Application	Inlet/Outlet (Fitting)	Max. Pressure (bar/psi)	Hose Capacity		Packing Dimensions(cm)	NW/GW (kgs)
				I.D.(inch)	Length(ft/m)		
L850153	Air reel	3/8"	20 bar / 300 psi	3/8"	50'/15	51x28x55	19/21
M850154	Oil reel	1/2"	138 bar / 2000 psi	1/2"	50'/15	51x28x55	20/22
H850152	Grease reel	1/4"	345 bar / 5000 psi	1/4"	50'/15	51x28x55	20.5/22.5

L850153

SPRING DRIVEN HOSE REEL - 860 SERIES

- ♣ Heavy ribbed steel plate to ensure strong support
- ♣ Special swivel joint for easy maintenance and repair
- ♣ Ball bearing swivel joint structure, largely reducing the friction between swivel spool and swivel body

Item No.	Application	Inlet/Outlet (Fitting)	Max. Pressure (bar/psi)	Hose Capacity		Packing Dimensions(cm)	NW/GW (kgs)
				I.D.(inch)	Length(ft/m)		
L860153	Air reel	3/8"	20 bar / 300 psi	3/8"	50'/15	51x28x55	21/23
M860154	Oil reel	1/2"	138 bar / 2000 psi	1/2"	50'/15	51x28x55	22/24
H860152	Grease reel	1/4"	345 bar / 5000 psi	1/4"	50'/15	51x28x55	22.5/24.5

L860153

SPRING DRIVEN HOSE REEL - 870 SERIES

- ♣ Heavy ribbed steel plate to ensure strong support
- ♣ Spring located in the middle to ensure stability of the reel
- ♣ Special swivel joint for easy maintenance and repair
- ♣ Ball bearing swivel joint structure, largely reducing the friction between swivel spool and swivel body

Item No.	Application	Inlet/Outlet (Fitting)	Max. Pressure (bar/psi)	Hose Capacity		Packing Dimensions(cm)	NW/GW (kgs)
				I.D.(inch)	Length(ft/m)		
L870153	Air reel	3/8"	20 bar / 300 psi	3/8"	50'/15	51x28x73	22/24
M870154	Oil reel	1/2"	138 bar / 2000 psi	1/2"	50'/15	51x28x73	23/25
H870152	Grease reel	1/4"	345 bar / 5000 psi	1/4"	50'/15	51x28x73	23.5/25.5

L870153

Note: For more information on hose reel, please refer to hose reel catalogue of ITI.