



## Air-operated Double Diaphragm Pumps

- Features an externally serviceable air distribution system and all-bolted construction
- Include ground capability to eliminate static discharge
- Both metal & plastic bodies are available
- A variety of elastomer options including Nitrile, Viton, EPDM & PTFE are available to meet abrasion, temperature, and chemical compatibility concerns.
- Maximum Diameter Solid: 1/8"



#17150500/#17150600



#17151200



Non included bracket for drum application



#17150501, #17150601

| Item No.        | Pump Material | Max. Flow Rate (GPM/LPM) | Max. Pressure (PSI/Bar) | Inlet/Outlet | Air Inlet |
|-----------------|---------------|--------------------------|-------------------------|--------------|-----------|
| <b>17150500</b> | Aluminum      | 12/45                    | 115/8                   | 1/2"         | 1/4"      |
| <b>17150501</b> | Plastic       | 12/45                    | 115/8                   | 1/2"         | 1/4"      |
| <b>17150600</b> | Aluminum      | 16/60                    | 115/8                   | 3/4"         | 1/4"      |
| <b>17150601</b> | Plastic       | 16/60                    | 115/8                   | 3/4"         | 1/4"      |
| <b>17151200</b> | Aluminum      | 20/90                    | 115/8                   | 1"           | 1/4"      |
| <b>17151201</b> | Plastic       | 20/90                    | 115/8                   | 1"           | 1/4"      |